


OS2 SC-SC UPC Duplex LSZH Patch Cord

SKU: FO-P-OS2-SCSC-DX · OS2 · single-mode · SC UPC to SC UPC



Single-mode OS2 duplex with SC connectors on both ends — the workhorse of central-office (CO) patching, GPON head-ends, and telecom SC bulkheads.

SPECIFICATIONS

Fiber type	OS2 single-mode, 9/125 μ m
Connector	SC UPC $\times$ 2 ends
Core count	Dual-core (duplex)
Jacket diameter	2.0 mm
Jacket material	LSZH
Insertion loss	$\leq$ 0.2 dB (typical)
Return loss	$\geq$ 50 dB (UPC single-mode)
Wavelength	1310 nm, 1550 nm
Distance	10 km+ (transceiver-dependent)
Durability	$\geq$ 1000 mating cycles
Standards	GR-326, IEC 61300, RoHS

AVAILABLE LENGTHS

1m 2m 3m 5m 7m 10m 15m 20m 30m 50m

STANDARDS

GR-326 · IEC 61300 · RoHS

ORDERING

Minimum order quantity: 100 units per SKU

Lead time: 3–5 days from stock · 1–2 weeks for custom lengths

Contact: sales@featheroptics.com · featheroptics.com

FeatherOptics · featheroptics.com · Specifications subject to change without notice.